

ESOTERIC®

WIREWORLD  
SABLE TECHNOLOGY  
Engineered for Heavens

Esoteric setup





**ESOTERIC D-02 DIGITAL SOURCE DECODER (DAC)** MSRP = \$23,500

- Eight AK 4399 32 bit Digital - Analog converters per channel
- Patent pending 32 bit digital processing algorithm
- Asynchronous USB input up to 192 kHz (supports 32 or 64 bit computer operating systems)
- Accepts 192 kHz/24 bit from P-02 (ES-Link) or 24 BIT/94 kHz sampling (Dual AES IFS)
- All class "A" discrete buffer amplifiers
- Four sub-linear laser selectable digital filters
- 32 Bit digital attenuator for connection direct to an amplifier
- Four separate power supplies separating digital and analog power systems for lowest noise
- "Direct Master Clock Link" with P-02 transport
- Master clock generator isolated from all other circuits
- Full "Dual Mono" design with separate chassis for each channel
- SN ratio of 108db and 0.0001% THD at 1kHz

Esoteric New D-02 DAC, P-05 Transport, E-30 Phono and K-05 SCD

# ESOTERIC

ESOTERIC K-05 DIGITAL SOURCE DEVICE/CD/SACD PLAYER MSRP = \$23,500

- SACD/CD player with VRDS-NEO VMK S
- 32-bit AKM4399 DAC
- Dual-Mono design: each channel is identical in architecture
- Digital inputs (coaxial, Optical and high speed USB) accepting up to 192 kHz 24 bit asynchronous data
- On-board master clock generator:  $\pm 3$  ppm accuracy. Also accepts external clocking signals
- Up sampling to 176.4 kHz 24 bit for CDs
- High quality buffer design

**Coming in 2012**

ESOTERIC's flagship one box solution



Close view Esoteric new K-05 SACD Player





Esoteric electronics with YG Kipod speakers in Synefgistics room



Esoteric

Esoteric®

ION  
by TEAC

Players  
CD-1000  
CD-2000

Esoteric D-02

Esoteric  
NO DISC

Super Audio  
P-C  
Stereo D-D  
D-C

Display with various Esoteric transports



**ESOTERIC. D-02** DIGITAL SOURCE DECODER (DAC) MSRP = \$23,500

- Eight AK 4399 32 bit Digital - Analog converters per channel
- Patent pending 32 Bit digital processing algorithm
- Asynchronous USB input up to 192 kHz (supports 32 or 64 bit computer operating systems)
- Accepts 192 kHz 48 Bit from P-02 (ES-Link3) or 24 BIT 384 kHz sampling (Dual AES SPI)
- All class "A" discrete buffer amplifiers
- Four different user selectable digital filters
- 32 Bit digital attenuator for connection direct to an amplifier
- Four separate covers supplies separating digital and analog power systems for lowest noise
- "Direct Master Clock Link" with P-02 transport
- Master clock generator isolated from all other circuits
- Full "Dual-Mono" design with separate chassis for each channel
- SN ratio of 100dB and 1000dB THD at 1 kHz



Close view D-02 DAC and P-05 Transport





Esoteric K-01 SACD in Convergent Audio System