





TRIGGER
THROUGH IN OFF ON
AUTO POWER SAVE

+ SPEAKER -
BTL + R
SPEAKER IMPEDANCE
STEREO (4-16Ω)/BTL (8-16Ω)
CLASS 2 WIRING

INPUT R
BTL

ESL-A

XLR
RCA

RCA

THIS DEVICE COMPLIES WITH PART 15 OF
THE FCC RULES. OPERATION IS SUBJECT
TO THE FOLLOWING TWO CONDITIONS:
(1) THIS DEVICE MAY NOT CAUSE HARMFUL
INTERFERENCE, AND (2) THIS DEVICE MUST
ACCEPT ANY INTERFERENCE RECEIVED,
INCLUDING INTERFERENCE THAT MAY
CAUSE UNDESIRABLE OPERATION.

CAN ICES-037(NAN003)



SIGNAL
GND



INPUT L
BI-AMP

ESL-A

RCA

XLR
RCA

~IN



INPUT SELECTOR

XLR

RCA

ESL-A

STEREO L R BI-AMP
BTL
OUTPUT MODE

- SPEAKER +
L BTL -
SPEAKER IMPEDANCE
STEREO (4-16Ω)/BTL (8-16Ω)
CLASS 2 WIRING

ROTHERIC
SERIAL NO.
TEAL CORPORATION JUNE 17, 2015





