

Bird SE

The First order crossover – in combination with the driver units – gives 100% time- and phase coherence and coincident.

The extreme rigid and resonance free cabinet have the same shape and similar performance as Coltrane Supreme 2.

You get 90% of the Coltrane Supreme 2 performance to a fraction of the price.



Bird SE - Technical Specifications

Frequency range / 24-100000 Hz +-2dB

Power rating / 300 W

Sensitivity / 87 dB / 1 m / 2.83V

Impedance / 6 ohm (3.4 Ohm min)

Type / 3-way bass reflex

Drive units / 3x7" aluminium sandwich, 1x5" ceramic, 1x0.75" diamond

Crossover frequency / first order: 370 & 4000 Hz

Terminals / WBT

Internal wiring / Jorma Design

Cabinet / 25-40 mm:s fibre laminate cabinet

Stands / Polished stainless steel with Marten pucks and cones

Dimensions (WxHxD) / 28 cm x107 cm x 38 cm

Net weight / 60 Kg

CHIEF DESIGNER:

Leif Olofsson

Bird SE

Supreme sound and elegance



MARTEN

HANDCRAFTED IN SWEDEN

Bird SE

The Cell Concept driver units are the same as in Coltrane Supreme 2.

The damping, polished stainless steel plate around tweeter and midrange unit is making use of the same technology as Coltrane Supreme 2.

The beautiful walnut wood veneer and the polished piano laquer finish is handcrafted to perfection.

The stands made of polished stainless steel.

The cones and pucks are made by Marten.

The Bird SE model is delivered in wooden crates.



MARTEN

HANDCRAFTED IN SWEDEN