

# MiniSub



## Overview

The Gil Mini Sub and Vision (AV version) has been designed as a complete system solution. The unit offers astonishingly simple plug-n-play installation. The rack width unit is compliant with all standard audio racking systems. At the rear of the unit are six high quality unswitched outlets, two high current for power amplifier use and four medium current featuring an extra levels of filtering for source components. The two models, Gil Mini Sub and Vision are tailored for either two channel or audio visual use.

Each outlet is individually filtered to not only protect delicate audio components from mains noise and dangerous power surges, but more importantly eliminate product cross contamination, an issue over looked by most filter companies. The two specific high current outlets featuring sophisticated shunt filtering to allow high current without dynamic restriction. The four remaining outlets feature a combination of shunt, series, delta, and protection filtering with gating and our proprietary 'Polaris-X' technology ensuring this is a highly effective unit.

## Key Features

- ✓ Shunt, Delta & Series filter networks
- ✓ 35dB & 58dB drop in digital noise
- ✓ 58dB Common Mode rejection
- ✓ Easy 'plug-n-play' set-up
- ✓ Suitable for all complete systems
- ✓ Component from component isolation
- ✓ 6 individually filtered outlets
- ✓ Elegant rack width chassis
- ✓ Multi award winning design
- ✓ UK, EU and US specifications available

## Specifications

Number of outlets: .....6  
 Type of outlets: .....UK, EU, US  
 Standard mains inlet: .....IEC fused  
 Mains voltage: .....100-240VAC/50-60Hz  
 Maximum current: (1 & 2) .....10Amps  
 Maximum current: (3 to 6) .....6.3Amps  
 Total maximum current: .....16.3Amps  
 External mains fuse: .....6.3Amps (13Amps UK)  
 Dimensions: .....444x85x305mm (WxHxD)  
 Weight: .....7.0Kg

