COMPACT DISC TRANSPORT
M1CDT
by MUSICAL FIDELITY
STANDBY
IR
UPSAMPLING D/A CONVERTOR
M1DAC
by MUSICAL FIDELITY
UPSAMPLING AT 192kHz
COAXIAL 2
COAXIAL 1
OPTICAL
USB
INPUT SELECT
POWER
32kHz
44.1kHz
48kHz
88kHz
96kHz
192kHz

COMPACT DISC
TRANSPORT
M1CDT
by MUSICAL FIDELITY
STANDBY
IR

COMPACT DISC
TRANSPORT
M1CDT
by MUSICAL FIDELITY
STOP. 3 69:04
STANDBY

CAUTION MOUNT UNIT ON SOLID SURFACE. DO NOT REMOVE SCREWS OR COVERS UNDER ANY CIRCUMSTANCES. NO USER SERVICEABLE COMPONENTS INSIDE. REFER SERVICING TO QUALIFIED ENGINEER. SEE OWNERS MANUAL FOR FURTHER INFORMATION.

DESIGNED IN ENGLAND BUILT IN TAIWAN

THIS PRODUCT COMPLIES WITH DHHS RULES 21 CFR, CHAPTER 1, SUBCHAPTER J, PART 1040 AT DATE OF MANUFACTURE.

THIS PRODUCT COMPLIES WITH PART 15 OF THE FCC RULES.
OPERATION IS SUBJECT TO TWO CONDITIONS:

1 THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND
2 THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRED OPERATION.

CLASS 1
LASER PRODUCT

INPUT VOLTAGE 90-250V
∿ 50/60Hz

THIS APPLIANCE MUST BE EARTHED
IMPORTANT

OPTICAL DIGITAL OUTPUT

COAXIAL DIGITAL OUTPUT

AES BALANCED DIGITAL OUTPUT

M1CDT CD TRANSPORT by MUSICAL FIDELITY

IN OUT
TRIGGER

POWER CONSUMPTION 10W

DATE OF MANUFACTURE

SERIAL NUMBER

CE