

REL
ACOUSTICS LTD.



212/SE
Sub-Bass
System

212/SE Specifications

Type:	Two front-firing active woofers, rear and down-firing passive radiator
Active Drive Units:	12 in., 300mm long-throw, die cast aluminium chassis
Passive Radiator Rear:	12 in., 300mm, die cast aluminum chassis
Passive Radiator Down:	12 in., 300mm
LF Response in Room:	21Hz at -6 dB
Input Connectors:	Hi Level Neutrik Speakon, Left and Right Lo Level phono, LFE phono, SMA connector for wireless antenna
Gain Control Range:	80 dB
Power Output:	1000 watts (RMS)
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Next Gen II Class D
Wireless capability:	Yes – REL Longbow™ transmitter [required]. Sold separately.
Protection System	
Fully Electronic with SET-SAFE:	Yes
D.C. Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	220-240 volts, 110-120 volts for certain markets
Fuses:	7 Amp semi delay 220 volts operation 15 Amp semi delay 120 volts operation
Dimensions (WHD):	Including feet and rear panel controls 17.2 x 32 x 20 in., (436 x 815.5 x 507 mm) Add 1.75in (44.5mm) in depth when using Hi Level connector
Net Weight:	122 lbs. (55.3 kg)
Shipping Weight:	TBD
Finish:	Gloss Piano Black
Supplied Accessories	
Mains Lead:	Yes
Neutrik Speakon Interconnect:	Yes (10 Meters Nominal)
Users Manual:	Yes

In the interest of product development, REL Acoustics Limited reserve the right to vary these specifications without notice



REL Acoustics Limited

North Road, Bridgend industrial Estate . Bridgend, CF31 3TP . United Kingdom

Telephone: +44 (0)1 656 768 777 . Fax: +44 (0) 1 656 766 093

Web: www.rel.net