

TANNOY®

Ever watched a movie without sound?



SFX10
HOME THEATRE SYSTEM



The real cinematic experience cannot even begin to happen without it.



Tannoy has engineered wide frequency bandwidth performance into this compact 5.1 Home Theatre system so that you will hear just what the sound engineer wanted you to hear; from a pin drop to a huge scale explosion this system accelerates effortlessly throughout the dynamic range.

Complete the audio picture.

The SFX5.1 satellite and centre channel speakers incorporate Tannoy WideBand™, technology which extends high frequency response up to 78kHz. This is not all about simply increasing the amount of high frequencies you hear. The purpose is to effect a reduction of phase error, not only at the top end of the frequency range, but also well within the range of human hearing for harmonic recognition.

What does this deliver?

Starting even as low as 5kHz, the effect of phase error reduction improves sonic detail, imaging precision and overall system integration. In 5.1 audio applications a wide bandwidth response improves the total acoustic performance of the system by delivering superior mid-band resolution and remarkable low frequency control. All this conveys music information with speed, impact and clarity. These essential acoustic characteristics are further enhanced during movie soundtrack reproduction through the provision of an involving and believable soundstage.

The natural voicing of the SFX5.1 system's four single driver satellites and one twin driver centre channel combine seamlessly with the powerful 100W active subwoofer. Aural effects and action sequences are delivered with impact, while speech localisation pans flawlessly left to right and front to rear.

SFX5.1 Home Theatre is available in black or silver, with colour matched floor stands available as optional accessories.

Centre & Satellites

PERFORMANCE

| | |
|---|--|
| Recommended amplifier power | 15 - 100 Watts |
| Maximum Sensitivity (2.83Volts @ 1m) | 85dB |
| Nominal impedance | 6 Ohms |
| Frequency response (-6dB) | 140Hz - 78kHz |
| Drivers | HF: 15mm (0.59") titanium dome, neodymium magnet system LF: 75mm (3.00") paper cone |
| Crossover frequency | 4.5kHz (mid to high) 140Hz (to subwoofer) |
| Magnetic shielding | Yes |
| Satellite Weight | 750gms (1.65lbs) |
| Satellite Dimensions H x W x D | 140 x 97 x 95mm (5.51 x 3.82 x 3.74") |
| Centre Weight | 1.5kg (3.3lbs) |
| Centre Dimensions H x W x D | 120 x 230 x 95mm (4.72 x 9.06 x 3.74") |
| Finish | Silver or black |
| Supplied accessories | Wall mounting brackets 25 metres (82ft 6") speaker cable |
| Optional accessories | Satellite floor stands available in matching silver or black |

Subwoofer

PERFORMANCE

| | |
|----------------------------------|--|
| Power output | 100 Watts |
| Frequency response (-6dB) | 45Hz - 140Hz |
| Driver | 200mm (8.00") paper cone |
| Inputs | Twin line or speaker level |
| Power requirements | 160VA max |
| Fuse ratings | AC100-120V / 60Hz - Fuse: T1.6A L /250V AC 220-240V / 50Hz - Fuse: T800mA L /250V |
| Additional features | ON / OFF/ AUTO power function |
| Weight | 9.0kg (20.0lbs) |
| Dimensions H x W x D | 345 x 250 x 370 mm (13.58 x 9.84 x 14.57") |
| Finish | Silver or black |



How it all adds up

| | | |
|-----------------------|--------------------------|-------------------------|
| Tannoy United Kingdom | T: 00 44 (0) 1236 420199 | E: enquiries@tannoy.com |
| Tannoy North America | T: 00 1 (519) 745 1158 | E: inquiries@tannoy.com |
| Tannoy Deutschland | T: 00 49 (180) 1111 881 | E: info@tannoy.com |
| Tannoy France | T: 00 33 (0)1 7036 7473 | E: ventes@tannoy.com |

Tannoy adopts a policy of continuous improvement and product specification is subject to change.

tannoy.com

6483 1029 / 0907