

03.M12

WEISS ENGINEERING
HSE AUDIO



HSE
SWISS

SA
SA
SA

SA
SA
SA

SA
SA
SA



HELIOS

- Flagship D/A Converter
- 192kHz, 32bit, S/PDIF, AES/EBU inputs
- Roon Ready
- Digital Signal Processor
- Equalizing, De-Essing, Integration, Creative Equalizing, De-Essing, Dynamics Adaptation, Virtual Simulation, Headphone Equalization, Cancellation, Crossfeed for Headphones
- Discrete Class A line and headphone outputs

DAC501

Versatile D/A Converter

- UPnP, DLNA, S/PDIF, AES/EBU inputs
- Digital Signal Processing for Room Equalizing, Creative Equalizing, De-Essing, Dynamics Adaptation, Virtual Simulation, Headphone Equalization, Cancellation, Crossfeed for Headphones
- 4-channel version: DAC501-4ch



Herbie Hancock on Weiss
I have been marvelling over how great
both products have been invaluable assets
to this project about peace through global cult

Mr. Herbie Hancock
Multiple Grammy Award-winning artist and musical icon
commenting on our A/D and D/A Converters in
The Imagine Project.

DAC20A

- DSD, ALPINE D/A Converter and Decoder
- DSD512, DSD256, DSD128, DSD64
- Sampling rates up to 32bit/384 kHz
- 110dB, Two inputs
- Four balanced outputs (XLR)
- Four unbalanced outputs (RCA)



HELOS

integrated

amplifier

with phono

and preamp

function

and DAC

function

and crossover

function

and volume

control

function

and tone

control

function

and balance

control

function

and bass

control

function

and treble

control

function

and volume

control

function

and crossover

function

and tone

control



WEISS

MAN301R
Integrated Amplifier
with Phono and Preamp
Function

WEISS

integrated

amplifier

with phono

integrated

amplifier

with preamp

function

and crossover

function

and tone

control

function

and bass

control

function

and treble

control

function

and volume

control

function

and crossover

function

and tone

control

DAC20A

- DSD, ALPINE D/A Converter and Decoder
- DSD512, DSD256, DSD128, DSD64
- Sampling rates up to 32bit/384 kHz
- 110dB, Two inputs
- Four balanced outputs (XLR)
- Four unbalanced outputs (RCA)

DAC20A

- DSD, ALPINE D/A Converter and Decoder
- DSD512, DSD256, DSD128, DSD64
- Sampling rates up to 32bit/384 kHz
- 110dB, Two inputs
- Four balanced outputs (XLR)
- Four unbalanced outputs (RCA)





SWISS

Made in
Switzerland



WEISS

ML-8

IMPEDANCE
GAIN

DAC501

HELIOS

David Bowie
00:00:00

DAC501

WEISS
Our Products in Action

AUDIO
PHONO
PSI
DSD

MODULES FOR ACTIVE SPEAKERS

Weiss Engineering offers three new modules created for high-end speakers.

DAC and A/D converters, completely ready to connect and ready for installation.

Power supply module for active speakers.

For more information visit our website.

PSU102

Analog Power Supply

- analog, non-switching
- very low noise / high speed regulation
- 115V / 230V mains voltage selectable
- 5V / 6V / 9V / 12V selectable at 1.5A

INT204

USB to AES/EBU and S/PDIF Interface

- DSD/D/A and DSD/D/S conversion
- up to 384 kHz sampling frequency
- Optical remote control for volume
- selectable sampling frequency for DSD to PCM conversion

DAC205

- S/PDIF Di/A Converter
- Sampling frequency up to 192 kHz
- RCA, Toslink inputs
- Analog outputs on XLR and RCA
- Four selectable output levels

MODULES FOR ACTIVE SPEAKERS




Weiss Engineering offers a range of OEM modules created for high-end speaker designs.

D/A and A/D converters, connectivity to various input and output formats, and DSP processing for crossover filters, EQing, and more. The modules and processing can be modified to suit the client's requirements.



Scan the QR
for more info!



PROUD MEMBER

ALTI
ASSOCIATION

Discover the
Quality of Music
in DSD

Visit our website
for more details
NativeDSD.com/FestCome



WEISS

